

蕨市民会館 DMX対応表

● 直調切替回路

H29.12.06 作成

DMX	回路名称	DMX	回路名称	DMX	回路名称			
1	1S 天反切替	-1	61	CL	-5	121	LH 下	-4
2		-2	62		-6	122	揚C 上	-1
3		-3	63		-7	123		-2
4		-4●	64		-8	124	揚C 下	-1
5		-5	65		-9	125		-2
6		-6	66		-10	126	予備	-1
7		-7	67		-11	127		-2
8		-8●	68		-12	128		-3
9	-9	69	FR 上	-1	129		-4	
10	-10	70		-2	130		-5	
11	-11●	71		-3	131		-6	
12	-12	72		-4	132		-7	
13	2S	-1	73		-5	133		-8
14		-2	74		-6	134		-9
15		-3	75		-7	135		-10
16		-4●	76		-8	136		-11
17		-5	77	FR 下	-1	137		-12
18		-6	78		-2	138		-13
19		-7	79		-3	139		-14
20		-8●	80		-4	140		-15
21	-9	81		-5	141	SC60 上●		
22	-10	82		-6	142	下●		
23	-11●	83		-7	143	予備		
24	-12	84		-8	144	//		
25	1BL 上下	-1	85	SC 上	-1●	145	客電最後方列(白熱球)	
26		-2	86		-2	146	客電LED 前方	-1
27		-3	87		-3	147		-2
28		-4	88		-4	148		-3
29		1BL 中	-1	89		-5	149	
30	-2		90		-6	150		-5
31	-3		91		-7	151		後方 -6
32	-4		92		-8	152		
33	2BL 上下		-1	93		-9●	153	
34		-2	94	SC 下	-1●	154		
35		-3	95		-2	155		
36		-4	96		-3	156		
37		2BL 中	-1	97		-4	157	
38	-2		98		-5	158		
39	-3		99		-6	159		
40	-4		100		-7	160		
41	TS		-1	101		-8	161	
42		-2	102		-9●	162		
43		-3	103	F	-1●	163		
44	-4	104		-2	164			
45	UH	-1	105		-3	165		
46		-2	106		-4	166		
47		-3	107	前C	-1	167		
48	-4	108		-2	168			
49	-5	109		-3	169			
50	-6	110		-4	170			
51	-7	111	後C	-1●	171			
52	-8	112		-2●	172			
53	-9	113		-3	173			
54	-10	114	LH 上	-1	174			
55	-11	115		-2	175			
56	-12	116		-3	176			
57	CL	-1	117		-4	177		
58		-2	118	LH 下	-1	178		
59		-3	119		-2	179		
60		-4	120		-3	180		